



Lubchem

WL-724/x4

Wireline Grease Seal – Enhanced Corrosive Service

Description:

Lubchem WL-724x4 Honey Oil is enhanced for severe corrosive service. 724x4 contains a superior corrosion protection package that includes a rust inhibitor, a downhole corrosion inhibitor, an H2S scavenger and pH buffers. This combination provides unequalled protection against corrosion in hot, high pressure down-hole environments where exposure to moisture, H2S, CO2 and corrosive acidic fluids occur. This grease is designed specifically for use in oil and gas well logging operations and other wireline applications where a lubricating dynamic seal is required.

Features:

- Enhanced corrosion package
- Hydrocarbon based
- Provides lubrication and sealing
- Minimizes loss of well fluids during operation
- Protects wireline against H2S and CO2
- Reduces drip and splatter
- Non-conductive
- Custom viscosities available on request

Applications:

WL-724x4 is inhibited for acid gasses and will protect wireline in conditions of 20% CO2 & H2S, high temperature and pressures to 10,000 psi and greater. Lubchem WL-724x4 is recommended for braided wireline, cables and wire rope. It is applied by grease injector control heads and cable lubricators and is available in the following viscosity grades and temperature ranges. Our 700x4 Series is available in 16 visc., 20 visc., 24 visc. and 28 visc.

Properties:

Appearance.....	Dark amber, viscous liquid
Density.....	7.5 lbs./gal. typical
Specific Gravity @ 25C	83-90
Flash Point (ASTM D92)	390F (198C)
Viscosity Range	21,500 to 24,400 cps@25C
Temp Range	70F (21C) to 150F (65C)