



ADDRESS:
23609 West Hardy Road
Spring, TX 77373

PHONE:
(800) 929-0244

EMAIL:
sales@lubchem.com

FACEBOOK:
facebook.com/lubchem

LINKEDIN:
@lubchem-inc

Technical Data Sheet

ProCoat 438

Filming Cable Lubricant/Protectant

Description:

ProCoat 438 Inhibited Cable Lube is formulated to protect braided cable from corrosion and deterioration during storage and transportation. This product forms a soft black film and protects wireline against rust, corrosion, and deterioration for up to six months or longer in severe conditions. ProCoat 438 Inhibited Cable Lube prevents rust and corrosion and includes an H₂S inhibitor for improved protection. The sulfonate corrosion inhibitor additive inhibits against calcium bromide, calcium chloride, zinc bromide and sea water.

ProCoat 438 contains molybdenum disulfide to provide protection to the core of the wireline. Apply with a pressure lubricator, spraying, brushing or wiping on the line. ProCoat 438 Inhibited Cable Lube is available in 5-gallon pails, 16-gallon drums, and 55-gallon drums and 275-gallon totes.

Advantages:

- Deposits water resistant films
- Easily cuts back in hydrocarbon solvents and oils
- Thin film formation allows fast drying
- Wash off Resistant
- Excellent shelf-life and long-term stability
- Displaces water

Physical Properties:

Color	Black
Specific Gravity	.88
Density	7.4 lb./gal
Flash Point	>288 F
Boiling Point.....	230-327 °C
Solubility	Oil soluble
Viscosity (Brookfield LVF)	2500 cPs
Shelf Life	2 years

Ordering Information:

P438-5	5 Gal. Drum
P438-16	16 Gal. Drum
P438-55	55 Gal. Drum
P438-275	275 Tote
P438-325	325 Tote