

ProCoat 435

Filming Cable Lubricant/Protectant

Description:

ProCoat 435 Inhibited Cable Lube is formulated to protect braided cable from corrosion and deterioration during storage and transportation. This product forms a soft clear film and protects wireline against rust, corrosion, and deterioration for up to six months or longer in severe conditions. ProCoat 435 Inhibited Cable Lube prevents rust and corrosion and includes an H₂S inhibitor for improved protection. The sulfonate corrosion inhibitor additive inhibits against calcium bromide, calcium chloride, zinc bromide and sea water.

Apply with a pressure lubricator, spraying, brushing or wiping on the line. ProCoat 435 Inhibited Cable Lube is available in 5-gallon pails, 55-gallon drums and 275-gallon totes.

Advantages:

- Deposits water resistant films
- Easily cuts back in hydrocarbon solvents and oils
- Wash off Resistant
- Excellent shelf-life and long-term stability
- Displaces water

Physical Properties:

Color Clear Amber
Specific Gravity88
Density 7.4 lb./gal
Flash Point >288 F
Boiling Point 230-327 °C
Solubility Oil soluble
NLGI Grade 0
Shelf Life 2 years

Ordering Information:

P435-5 5 Gal. Pail
P435-55 55 Gal. Drum
P435-275 275 Tote
P435-325 325 Tote